



Specifications	CC8800-C (Std.)	CC8800-E (Mini)	CC8800-F (D3.1)	CC8800-D (indoor)
Dimensions	15.55" x 10.04" x 5.07"	10.43" x 7.68" x 5.98"	17.13" x 9.65" x 7.28"	19.02" x 11.81" x 1.73"
Unit Weight	20.50 lbs.	11.02 lbs.	35.49 lbs.	9.48 lbs.
Shipping Weight	24.91 lbs.	11.68 lbs.	39.68 lbs.	13.89 lbs.
Channel Bonding	16 DS 4 US	16 DS 4/2 US	3.0: 64 DS 12 US 3.1: 6 DS 2 US"	16 DS 4 US
RF Interface	4 RF OUT (4 TV IN)	2 RF OUT (1 TV IN)	4 RF OUT	1 DS port, 4 US port
Max Output	4 In 4 Out Type: ≤ 108dBuV Optical RX Type: ≤ 112dBuV	4 In 4 Out Type: ≤ 108dBuV Optical RX Type: ≤ 104dBuV"	112dBuV	≤ 104dBuV
Power Supply	AC110V/AC220V local AC60V/AC90V by cable	AC110V/AC220V local AC60V/AC90V by cable	AC110V/AC220V local AC60V/AC90V by cable	AC220V/AC110V local
Power Consumption	90W	50W	115W	50W
Operating Temp Range	-40° to 131°F	-40° to 131°F	-40° to 131°F	-40° to 131°F
Waterproof	IP67	IP67	IP67	N/A
Lightning Protection	6000V	6000V	6000V	N/A
DOCSIS Support	DOCSIS 2.0 / 3.0	DOCSIS 2.0 / 3.0	DOCSIS 2.0 / 3.0 / 3.1	DOCSIS 3.0 / 3.1
No. of CM Supported	≤ 500	≤ 500	DOCSIS 2.0/3.0 ≤ 1000 DOCSIS 3.1 ≤ 300"	DOCSIS 2.0 ≤ 500 DOCSIS 3.0 ≤ 200"



MANAGED BROADBAND SERVICES
1.800-909-9441
 4501 North Point Parkway, Suite 125
 Alpharetta, GA 30022
 ZCorum.com
 Facebook.ZCorum.com
 Twitter.com/ZCorum